

OCXO Small Size

Features

- Ultra Stable
- Wide Temperature Range
- SMD(9.0mm*7.0mm)

Temperature Stress Test	IEC60068, GJB360B
Mechanical Stress Test	IEC60068, GJB360B
EMC Test (ESD)	IEC61000, JESD22
Solder Ability	EIA/JESD22-B102-C
RoHS	RoHS Directive 2011/65/EU Annex II Recasting 2002/95/EC

Features	Tight Stability Low Phase Noise
Dimensions	9.0x7.0 / 7,0 x 5,0 mm
Freq. Range	10MHz~200MHz
Freq. Stability Range	±3ppb~±500ppb
Phase Noise Range	-170dBc/1kHz@10MHz -165dBc/1kHz@100MHz

Specifications general

Wide temperature, low phase noise, low consumption, small size

Type	Operating temp. (°C)	Freq. tolerance (ppb)	Ageing (Day)	Ageing (Year)	Phase noise (dBc/Hz@1K)	Dimension (mm)	Standard Freq. (MHz)
O11F	-40 ~ +95	±3.0	±1.0	±0.1	-158	SMD 14.4*9.5*6.5	10/12.8/19.2/20/25 30.72/38.88/48
	-55 ~ +105	±10.0	±3.0	±0.2	-158	SMD 14.4*9.5*6.5	
O79A	-40 ~ +95	±5.0	±1.0	±0.1	-155	SMD 9.7*7.5*3.9	
	-55 ~ +105	±10.0	±3.0	±0.2	-155	SMD 9.7*7.5*3.9	
O75A	-40 ~ +95	±10.0	±3.0	±0.1	-155	SMD 7.5*5.5*3.3	
	-55 ~ +105	±20.0	±3.0	±0.2	-155	SMD 7.5*5.5*3.3	

- Please consult us for customized and detailed specifications.