



OCXO Wide Temp Range , Small Size

Features

- Wide temperature, low phase noise, low consumption, smallest size

Applications

- Wire communication
- Wireless communication
- Private power network
- Industrial control
- Instruments etc.
- Surface mount package
- Various supply Voltages Available
- Voltage control function
- RoHS Compliant, Lead Free Construction

Specifications general

Type	Operating temp. (°C)	Freq. tolerance (ppb)	Ageing (Day)	Ageing (Year)	Phase noise (dBc/Hz@1K)	Dimension (mm)	Standard Freq. (MHz)
O11F	-40 ~ +95	±3.0	±1.0	±0.1	-158	SMD 14.4*9.5*6.5	10/12.8/19.2/20/25 30.72/38.88/48
	-55 ~ +105	±10.0	±3.0	±0.2	-158	SMD 14.4*9.5*6.5	
O79A	-40 ~ +95	±5.0	±1.0	±0.1	-155	SMD 9.7*7.5*3.9	
	-55 ~ +105	±10.0	±3.0	±0.2	-155	SMD 9.7*7.5*3.9	
O75A	-40 ~ +95	±10.0	±3.0	±0.1	-155	SMD 7.5*5.5*3.3	
	-55 ~ +105	±20.0	±3.0	±0.2	-155	SMD 7.5*5.5*3.3	

- Please consult us for customized and detailed specifications.